

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 March 2004 (11.03.2004)

PCT

(10) International Publication Number
WO 2004/021512 A1

(51) International Patent Classification⁷: **H01Q 3/01**,
21/00, G01S 3/38

(21) International Application Number:
PCT/SE2002/001550

(22) International Filing Date: 30 August 2002 (30.08.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **TELEFONAKTIEBOLAGET LM ERICSSON [SE/SE]**;
S-126 25 Stockholm (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **NUMMINEN, Michael [SE/SE]**; Gyllenstjärmans väg 8A, S-371 40 Karlskrona (SE).

(74) Agents: **ALBIHNS GÖTEBORG AB et al.**; Box 142, S-401 22 Göteborg (SE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD FOR ENHANCING THE MEASURING ACCURACY IN AN ANTENNA ARRAY



(57) Abstract: The invention refers to a method and a system for enhancing the measuring accuracy in an antenna array (1), where the method comprises the steps of; a) receiving analog signals on all antenna elements (2) at a first time t_1 ; producing first values for a first radiation diagram from the values in the signals from the first time (t_1), and; finding the maximum point (8) for the first values, b) -reducing the signal from one interadjacent antenna element (2) at a second time (t_2); receiving analog signals on all antenna elements (2) except from the one switched off or reduced antenna element, and; producing second values for a second radiation diagram from the values in the signals from the second time (t_2); c) rejecting all values outside a first range (9) calculated from the first values, and; finding the maximum point (8) for the second values.